POSICHARGE[™] SVS100



Single Port. Dedicated. Compact. Intelligent Fast Charge

Posicharge SVS100 is a compact charger and a great fit for a variety of electric airport ground support equipment that require fast or opportunity charging. Typical customers for this charger include regional jet organizations, GA and FBO airport operators, and other non-hub maintenance and logistics companies. The SVS100 is outdoor-rated to withstand extreme environmental conditions. The SVS100 can provide up to 10kW of power in a single port, which is ideal for small electric belt vehicles, as well as for carts and people movers.

Our unique technology utilizes battery voltage and temperature sensors to accurately control the charging profile, adding an unparalleled layer of efficiency and safety.

The SVS100 features IGBT technology for high performance and reliability. And like all Posicharge chargers, the SVS100 works with a broad range of battery voltages, types, and capacities for virtually any vehicle application. In addition, the chargers also capture the data required to analyze and manage individual and fleet vehicle battery status and usage.



eGSE

KEY OPTIONS

CEC CERTIFICATION - Chargers meet CEC round trip efficiency and idle power standards required by certain states.

BATTERY RX[™] – Advanced battery monitor for maximum battery life with optional cellular connectivity and data services.

POSINET[™] – Works with cellular Battery Rx to collect battery charge data and run usage reports.



in 🗗 🕑 🔠



PROCEED WITH CERTAINTY PosiCharge[™] systems, a product line of AeroVironment, Inc. 1.866.767.4242 | info@posicharge.com © 2017 AeroVironment, Inc. posichargeprocore.com @posicharge posicharge.com

POSICHARGE™ SVS Single-Vehicle System **ADVANTAGE**

- Intelligent system designed to maximize available electrical infrastructure, keep fleet operational 24/7 and maintain battery health
- » Lower infrastructure costs compared to large scale single-vehicle systems
- » Lower maintenance & operational cost
- » Affordable stand-alone solution for small or remote fleets
- » Extended battery life & run time
- » Euro and Burton Output Connector/Cable Options





SPECIFICATIONS

	SVS100
POWER RATING	10kW
UTILITY REQUIREMENTS*	480/600 VAC, 3-PHASE
FULL LOAD AMP DRAW	15A / 12A MAX
MAX CIRCUIT BREAKER RATING	20A / 15A
POWER FACTOR	0.98
EFFICIENCY	91%
BATTERY VOLTAGE RANGE	24V - 80V
MAX OUTPUT CURRENT	250A
WEIGHT	388 LBS
DIMENSIONS	39.4"H X 22"W X 19.3"D

HIGHEST SAFETY STANDARDS: CE, UL1012, CSA

03062017r1

AeroVironment[™] PROCEED WITH CERTAINTY PosiCharge[™] systems, a product line of AeroVironment, Inc. 1.866.767.4242 | info@posicharge.com © 2017 AeroVironment, Inc. posichargeprocore.com @posicharge posicharge.com

All specifications are subject to change, image shown is a representation; production model may vary slightly in appearance

