

PosiCharge™ MVS 330

Multi-Vehicle System Charger



Multi-port, multi vehicle fast charge system

The MVS 330 is especially designed to lower utility costs and maximize available infrastructure. An MVS 330 can charge up to 8 industrial vehicles (e.g. tow tugs, baggage tractors, belt loaders, etc.) at the same time. This cost saving alternative to conventional charging makes implementing and using electric GSE vehicles more cost effective. The more vehicles charged at once, the greater the cost benefit.

Like the DVS, MVS features the highest power quality and most diverse multi-voltage, multi-ampereage flexibility of any fast charging system available today. MVS systems are installed all across the world's largest airports, as well as Fortune and Global 100 companies. And like all PosiCharge chargers, the MVS 330 works with a broad range of battery voltages and has the same data management and onboard intelligence.

Key Features:

- Smart Battery Monitor and Identification Device (BMID)
- Charge different vehicles or batteries on the same charger
- Flexible up to 8-vehicle charge option
- Charge 3x the equipment with the same power used for conventional chargers
- Euro and Burton output connector/cable options
- Automatic start/stop
- Anti-arcing disconnect
- Auto thermal shutdown
- High efficiency IGBT technology
- Lower maintenance and operational cost
- Easy to install, easy to use

Technical Specifications

	MVS 330: Powerserver
Power Rating	33kW
Utility Requirements	380 / 400 / 415 VAC, 3-phase
Full Load Amp Draw	56A / 53A / 51A
Max Circuit Breaker Rating	64 A
Power Factor	0.96
Efficiency	90%
Weight	915 lbs
Dimensions	60"H x 32.4"W x 21.9"D

	PowerStation
Power Rating	60kW
Battery Voltage Range	24V - 96V
Max Output Current (Dual Mode)	250A
Max Output Current (Single Mode)	500A
Weight	304 lbs
Dimensions	30"H x 30"W x 19"D
Communication Port	RS232