

ProCore™

Premium Intelligent Charging System



Maximum Performance. Unparalleled Safety.

The PosiCharge ProCore™ Series is a premium intelligent charging family that supports and charges any material handling battery - regardless of type, brand, chemistry, voltage or size. With power ranges from 5kW to 30kW, multi-voltage flexibility and value added options, ProCore is ideal for your entire fleet.

A small, lightweight, powerful, highly efficient charger, ProCore is easy to use and provides extreme flexibility with multiple customization options. It takes up minimal floor space and requires no specific training to mount, install, and update.

ProCore's powerstage modules offer scalability for any forklift fleet - from the smallest to the largest operations. ProCore's modular design makes it easy to service, upgrade, troubleshoot, and repurpose, and its robust architecture makes it highly customizable. Compatible with both BMID and non-BMID and CAN devices.

High peak efficiency combined with low overcharge factor make ProCore the most efficient charger available with the lowest monthly utility costs.

Key Features:

- Certified to the highest industry product safety standards.
- Lighter weight for easier installation and additional mounting options
- Multi-input breaker selection offers installation flexibility and upgrade capability
- CEC tested and certified by exceeding the minimum efficiency and idle power consumption set by the California Energy Commission
- Power management tool enables full programmability to plan for peak utility demand periods
- CAN/PLC capability enables chargers to talk to AGVs and mobile robots, and advanced batteries such as lithium
- Real time battery temperature / voltage monitoring and compensation enable precise charge control of batteries for fastest and safest charging
- Stacklight options – for visual notifications of the battery/charger status
- Autowater control options for optimal battery watering during the equalization cycle

ProCore™ and Advanced Connect Rx

ProCore™ with Advanced Connect Rx™ combines a sophisticated charge algorithm, battery thermal management and anti-arc technology for unparalleled safety and performance.

Mobile Access and Control

Through an innovative mobile app, connecting with, programming and downloading data from ProCore can be done from a smartphone running iOS or Android. This tool allows remote set up of new units, troubleshooting, and makes changes to your fleet simple.

Technical Specifications

| Power Rating | 5 kW | 10 kW | 15 kW | 20 kW | 30 kW w/ single cable | 30 kW w/ dual cable | 30 kW w/ dual cable |
|--|-------------------|-------------------|-------------------|-------------------|--------------------------|------------------------|------------------------|
| Max Output Current 24 / 36 / 48 V | 160 / 111 / 83 | 200 / 200 / 167 | 320 / 320 / 250 | 400 / 400 / 320 | 400 / 400 / 400 | 500 / 500 / 500 | 600 / 600 / 600 |
| Max Output Current 48 / 72 / 80 V | N/A | 160 / 111 / 100 | 250 / 167 / 150 | 320 / 222 / 200 | 400 / 333 / 300 | N/A | N/A |
| Circuit Breaker at 480 VAC | 10A | 20A | 25A | 40A | 50A | 50A | 50A |
| Idle Power | <10W | <10W | <10W | <10W | <10W | <10W | <10W |
| Dimensions, H x W x D | 31.5"x 20"x 10.5" | 31.5"x 20"x 10.5" | 31.5"x 20"x 15.2" | 31.5"x 20"x 15.2" | 31.5"x 20"x 20" | 31.5"x 20"x 20" | 31.5"x 20"x 20" |
| Weight (lbs) | 86 lbs | 91 lbs | 144 lbs | 144 lbs | 190 lbs | 196 lbs | 206 lbs |
| Input Voltage SKUs for Nominal 380V, 400V, 415V, 440V, 480V (50/60HZ) | Y | Y | Y | Y | Y | Y | Y |

PosiCharge is a product line of
Webasto Charging Systems, Inc.
1333 S. Mayflower Avenue,
Suite 100
Monrovia, CA 91016
USA

+1 (888) 767-4242

posicharge.com